






All of our Monitor scan tools use adapter cables to connect them to the vehicle system you need to test. Also, adapter cables will connect the more popular computers to the Monitor's serial interface port.












Enhanced Monitor

213492  
WYSE-60  
printer  
cable










Accessory	Number	Description
 IBM AT	212535	DB-9 20-ft. 9-pin connector Wt., 10 oz.
 Display Terminal	213479	WYSE-60/Bear B.A.C.E. 20-ft. adapter cable Wt., 3 oz.
 Hard-Copy Printer	212536	DB 25 20-ft. 25-pin connector Wt., 10 oz.
 Bear B.A.C.E.	213479	WYSE-60/Bear B.A.C.E. 20-ft. adapter cable Wt., 3 oz.
 IBM PC or XT	212536	DB 25 20-ft. 25-pin connector Wt., 10 oz.

## Monitor Scan Tool Adapter Cables and Accessories *(Continued on next page)*

### GENERAL APPLICATIONS

	Number	Description
	212535	DB-9 20-ft. 9-pin connector. Connects Monitor directly to an IBM AT personal computer. Wt., 9 oz.
	212536	DB-25 20-ft. 25-pin connector. Connects Monitor to hard-copy printer or IBM PC or XT personal computer or Bear P.A.C.E. Wt., 9 oz.
	212541	"Y" battery connector. Used for splitting the power supply from the cigarette lighter or 12-volt power supply to the Monitor, printer, or other accessories. Wt., 4 oz.
	212636	6-ft. vehicle extension cable for Monitor 4000E or 2000 only. Wt., 5 oz.
	212637	6-ft. power extension cable for use with Monitor, Communicator, or printer. Wt., 6 oz.
	212638	Battery adapter for Monitor. Used for under-hood access to 12-volt power supply. Wt., 4 oz.
	212641	12-volt power supply. Use when battery power is unavailable and you need to review data from the Monitor, printer, or Communicator. Wt., 1 lb., 4 oz.
	213479	WYSE-60/Bear B.A.C.E. 20-ft. adapter cable. Used with Monitor, WYSE-60 video display terminal and/or Bear B.A.C.E. console analyzer. Wt., 9 oz.
	213492	WYSE-60 printer cable. Used to connect the auxiliary port of the WYSE-60 video display to the hard-copy serial printer. Wt., 4 oz.
	3305-71	DB-25 extension cable. Used with Enhanced Monitor 4000 only, to connect 25-pin Monitor adapter cables. Wt., 13 oz.
	3305-72	DB-25 to 8-pin DIN extension cables. Used with Enhanced Monitor 4000 only, to connect 8-pin vehicle adapter cables. Wt., 12 oz.

### SYSTEM SMART CABLES AND INSERTS

SSI 8-Pin	Number	Description	Applications
	3305-86	System Smart 8-pin cable Wt., 14 oz.	Must be used with Monitor 4000E. Used with 8 pin SSI.
	3306-02	GM System Smart Insert Wt., 2 oz.	LT-1 '94-'95 Buick 3800 '94-'95
	3306-04	Chrysler System Smart Insert Wt., 2 oz.	Chrysler Neon '95-curr. Chrysler '96-curr.
	3306-06	GM Slow Baud System Smart Insert Wt., 2 oz.	LT-1 '94-'95 Buick 3800 '94-'95 GM non-engine systems
SSI 25-Pin	Number	Description	Applications
	3305-73	System Smart 25-pin cable Wt., 13 oz.	Must be used with Monitor Enhanced. Used with 25-pin SSI.
	3306-01	OBD II System Smart Insert Wt., 2 oz.	Generic OBD II '95-curr.
	3306-03	GM System Smart Insert Wt., 2 oz.	LT-1 '94-'95 Buick 3800 '94-'95
	3306-05	Chrysler System Smart Insert Wt., 2 oz.	Chrysler Neon '95-curr. Chrysler '96-curr.
	3306-07	GM Slow Baud System Smart Insert Wt., 2 oz.	LT-1 '94-'95 Buick 3800 '94-'95 GM non-engine systems

## Scan Tool Adapter Cables and Accessories *(Continued on next page)*

### DOMESTIC APPLICATIONS

GM	Number	Description	Model	Year
	212550	Adapter block (Gray) Wt., 3 oz.	GM 5-pin diagnostic connectors	'81-'82
	212633	GM 14" vehicle adapter cable Wt., 3 oz.	GM most systems	'82-'95
	212653	Tuned port inj. adapter cable (Gray) Wt., 4 oz.	GM 5.0L TPI GM 5.7L TPI GM 2.8L V6 P4	'86 '86-'89 '87-'88
	213486	UNIV B 12" adapter cable Wt., 4 oz.	GM ABS Teves II and Kelsey Hayes	'88-'94
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	GM 4.3L GM ABS	'80'1/2 '88-'95
	3305-17	Geo/Isuzu adapter cable Wt., 6 oz.	GM Geo & Spectrum GM Isuzu and Luv	'87-'95 '81
	3305-18	UNIV 80 adapter cable Wt., 3 oz.	GM 3.8L	'80'1/2
Ford	Number	Description	Model	Year
	212634	Standard 14" adapter cable Wt., 4 oz.	Ford EEC-IV and MCU, ABS, Suspension for '92 or older software	'81-'92
	3305-58	Ford II 14" adapter cable (Gray) Wt., 6 oz.	Ford EEC IV MCU, ABS, Suspension used with Pathfinder II or newer software	'81-'95
	3305-84	Ford III, 25-pin, 18" cable (red) with 4' power lead. Wt., 10 oz.	Ford EEC IV ABS, Suspension used with Pathfinder III or newer software	'83-'95
	3305-104	Ford IV, DCL cable 25-pin, 18" cable (red) with 4' power lead. Wt., 10 oz.	Ford EEC IV, Fast code, engine management only Pathfinder III or newer software	'89-'95
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	Ford EEC II & III	'79-'83
	3305-74	Universal "C", 8-pin, 12" cable Wt., 4 oz.	Ford/Mazda mfd. vehicles, ABS	'93-'94
	213596	MECS 6" adapter cable Wt., 4 oz.	Ford/Mazda mfd. vehicles	'88-'95
	3305-14	MET adapter cable Wt., 6 oz.	Ford/Mazda mfd. vehicles	'91-'95
	3305-19	MECS ABS adapter cable Wt., 2 oz.	Ford/Mazda ABS	'89-'93
Chrysler	Number	Description	Model	Year
	212635	Standard 12" adapter cable Wt., 4 oz.	Chrysler	'84-'95
	3305-63	Chrysler II 14" adapter cable Wt., 6 oz.	Chrysler LH models	'93-'95
	3305-65	Chrysler III 25-pin, 18" cable Wt., 12 oz.	LH Chrysler CCD with 4000 Enhanced	'93-'95 '88-'95
	3305-22	Chrysler CCD 14" adapter cable Wt., 10 oz.	Chrysler CCD with 4000E	'88-'95
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	Chrysler Import/ 2/3/9-pin connector Colt Conquest TSI	Most '85-'94 '84-'86

### DOMESTIC APPLICATIONS *continued*












Chrysler	Number	Description	Model	Year
	216094	Universal test leads Wt., 2 oz.	Chrysler/Mitsubishi	
	3305-20	Mitsubishi/Hyundai cable Wt., 3 oz.	Most	
	3305-92	Chrysler OBD II "Y" adapter	Used on Talon, Avenger, & Sebring Wt., 4 oz.	'95, '96
	3305-93	Chrysler OBD II to 6 pin adapter	Used for accessing CCD systems at the J1962connector. Wt., 4 oz.	'95, '96

### IMPORT APPLICATIONS










	Number	Description	Model	Year
	212633	GM 14" adapter cable Wt., 3 oz.	Isuzu Pickup (3.1L) Rodeo Trooper II	'91-'95 '91-'95 '89-'95
	213486	UNIV B cable 12" adapter cable Wt., 4 oz.	Geo/Metro Suzuki/Swift	'91-'95 '89-'95
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	Mitsubishi Starion Mirage Galant Cordia Tredia	'84-'86 '85-'95 '85-'95 '84-'95 '84-'95
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	Suzuki Swift GT Swift Geo/Metro	'90-'95 '89-'95 '89-'95
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	Daihatsu Charade Rocky	'89-'95 '90-'95
	213487	CARB/UNIV A 12" adapter cable Wt., 4 oz.	Chrysler Colt Conquest TSI	'84-'94 '84-'86
	3305-68	Honda/Acura Jumper Wt., 2 oz.	Honda Acura	'89-'95 '91-'95
	213596	MECS 6" adapter cable Wt., 5 oz.	Mazda	'83-'95
	3305-14	MET adapter cable Wt., 6 oz.	Mazda 323/Protege 929 Miata MX-3	'90-'95 '92-'95 '90-'95 '92-'95
	216044	Nissan 12" adapter cable Wt., 4 oz.	Nissan	'87-'95
	3305-66	Nissan/Infiniti Jumper Wt., 3 oz.	Infiniti and Q-45 G-20, M-30 Nissan 300ZX Stanza 240SX NX Sentra Maxima	'90-'95 '90-'93 '90-'95 '90-'92 '91-'94 '91-'93 '91-'94 '94

## Scan Tool Adapter Cables and Accessories

### IMPORT APPLICATIONS *continued*

	Number	Description	Model	Year
	3305-13	Lexus/Toyota adapter cable. Includes auxiliary probe and power adapter. Wt., 10 oz.	Toyota, Lexus Lexus-Engine Camry-Engine Cressida-Engine Lexus MR2 Cressida Supra Camry Celica Corolla Starlet Truck 4Runner Van	'90-'93 '92-'94 '89-'92 '90-'93 '85-'91 '83-'92 '83-'91 '83-'94 '85-'91 '85-'91 '83-'84 '85-'91 '91 '90
	3305-16	Toyota adapter cable Wt., 5 oz.	Toyota Cressida Supra	'83-'84 '83-'84
	3305-15	Subaru adapter cable Wt., 6 oz.	Subaru SPFI MPFI (Except Justy) EFC (Justy)	'87-'93 '88-'93 '88-'90
	3305-17	Geo/Isuzu adapter cable Wt., 6 oz.	Isuzu I-Mark (Fuel Inj.) I-Mark (Carb.) I-Mark Impulse Pickup, Amigo (2.3 & 2.6L) Rodeo Trooper II	'88-'89 '87-'89 '85-'86 '84-'92 '88-'93 '91-'93 '89-'91
	3305-17	Geo/Isuzu adapter cable Wt., 6 oz.	GM Import Spectrum Storm Geo/Metro	'87-'89 '90-'93 '90-'93
	3305-69	Geo/Isuzu Jumper Wt., 4 oz.	Samurai Geo/Metro	'89-'93 '89-'93
	216094	Universal test leads Wt., 2 oz.	Diahatsu, Mitsubishi Hyundai	'89-'92 '85-'88
	3305-48	Mitsubishi/DS adapter cable Wt., 8 oz.	Mitsubishi Diamante Precis 3000GT Truck Eclipse Starion Mirage Montero Van Sigma Galant	'92-'93 '90-'93 '91-'93 '89-'93 '90-'93 '87-'89 '89-'93 '89-'93 '87-'90 '89-'91 '87-'93
	3305-48	Mitsubishi/DS adapter cable Wt., 8 oz.	Chrysler Import Stealth D50 Truck Laser Vista Talon Coit Summit Raider Conquest TSI	'91-'93 '91-'93 '91-'93 '89-'93 '90-'93 '88-'93 '89-'93 '89 '87-'89
	3305-48	Mitsubishi/DS adapter cable Wt., 8 oz.	Hyundai Sonata Scoupe Excel (MPI only)	'89-'93 '91-'92 '90-'92
	3305-19	MECS ABS Cable Mazda ABS Wt., 8 oz.	626/MX-6 MX-3	'92-'93 '92-'93

### TECH 2 FLASH

	Number	Description
	3000095	DLC cable used with Tech 2 Flash adapter, 10'. Wt., 1 lb., 8 oz.
	3000096	Cigarette lighter power cable Wt., 4 oz.
	3000097	Battery adapter power cable Wt., 10 oz.
	3000098	OBD II 16 pin DLC adapter. '95 to curr. OBD II. Wt., 4 oz.
	3000099	GM 12 pin NAO DLC adapter '82-'95 GM applications. Wt., 4 oz.
	3000109	DLC loopback adapter for Tech 2 Flash troubleshooting. Wt., 4 oz.
	3000113	110 volt to 12 volt converter. Wt., 1 lb., 8 oz.
	3625-04	DLC to OTC adapter used to adapt OTC Ford and Chrysler cables to Tech 2 Flash DLC cable. Wt., 7 oz.
	3625-05	Adapter for Chrysler Neon application, 12" Wt., 7 oz.